

InfoLink Option Selector Guide

Key Specifications				
Product	Code [2]	Description	Key specification	
12A/ [code]	S	External memory 64Kbit	Low power SRAM	
	X4	400MHz telemetry link transmitter	0dBm typical output	AFSK modulation. 25KHz B/W
	X8	800MHz telemetry link transmitter	0dBm typical output	AFSK modulation 25KHz B/W
	X23	2300MHz telemetry link transmitter	-10dBm typical output	FSK modulation 25KHz B/W
	V5	Fixed 5Volt operation	+/-5%	
	V9	7-16Volt operation	Linear regulator	
	V30	7-40Volt operation	SM regulator	
	T [1]	Trigger outputs available on RB9 way connector	Pin 1 = Trig A (TTL) Pin 9 = Trig B (o/coll)	PCB Links Z23, Z22
	P [1]	Power on RB9 way D connector	Pin 4 = +ve Pin 6 = -ve (gnd)	PCB Links Z20, Z21

NOTES

1. # Do not indicate T or P options if 12A is to be connected to a RS-232 standard interface.
2. Each code is specified sequentially (any order, but preserve integrity). E.G. 12A/SX4.

See [Specifications](#) for more details.

Please contact us, we'll be pleased to provide additional information

Telephone: +44 (0)1296 682552

Facsimile: +44 (0)1296 682551

<mailto:data@datanet.org.uk>